## AMENDMENT TO THE CLAIMS

1.    (Currently Amended) An apparatus for cache flushing, comprising:

a list structure for tracking the status of a plurality of cache entries, wherein

said list structure is located outside the cache <u>and wherein said list structure does not</u>

<u>contain cache data or addresses</u>;

a query mechanism for checking said list structure for the state of a cache entry;

and

a cache flush mechanism, logically coupled to said list structure and the cache, for

flushing a cache entry and for modifying said list structure to reflect the flushed state.


2.    (Original) An apparatus in accordance with claim 1, wherein:

said list structure comprises one bit per cache line.


3.    (Original) An apparatus in accordance with claim 1, wherein:

said list structure comprises one bit per plurality of cache lines.


4.    (Original) An apparatus in accordance with claim 1, wherein:

said list structure comprises one bit per cache way.


5.    (Original) An apparatus in accordance with claim 1, further comprising:

one bit per a variable number of cache lines; and

wherein the logical arrangement of said list structure conforms to said variable number.

6.    (Original)  An apparatus in accordance with claim 5, wherein:

said variable number is set by an operating system.

7.    (Currently Amended)  An apparatus in accordance with claim 1, wherein:

the a logical arrangement of said list structure matches the architecture of a cache.

8.    (Original)  An apparatus in accordance with claim 1, wherein:

said cache flush mechanism modifies a cache state responsive to the results of a query of the said list structure.

9.    (Original)  An apparatus in accordance with claim 8, wherein:

said cache flush mechanism is logically coupled to a higher level cache for writing back modified data.

10.    (Original)  An apparatus in accordance with claim 8, wherein:

said cache flush mechanism based on the said list structure is logically coupled to a higher level cache for evicting modified data.

11. (Original) An apparatus in accordance with claim 8, wherein:

said cache flush mechanism is logically coupled to the main memory for writing back modified data.

12. (Original) An apparatus in accordance with claim 8, wherein:

said cache flush mechanism is logically coupled to the main memory for evicting modified data.

13. (Original) An apparatus in accordance with claim 1, wherein:

said list structure is located in random access memory (RAM).

14. (Currently Amended) An apparatus in accordance with claim 1, wherein:

said list structure is located on ~~the~~ a die.

15. (Original) An apparatus in accordance with claim 1, further comprising:

a snoop command interpreter for checking said list structure in response to a snoop command.

16. (Currently Amended) In a computer system with a cache memory, an apparatus for flushing the cache, comprising:

a list structure for recording modifications to a plurality of cache entries wherein

said list structures does not contain cache data or addresses;

a cache controller adapted to query said list structure for modifications to said plurality of cache entries and generate a list of cache write-back instructions; and

wherein said cache controller invalidates said plurality of cache entries corresponding to said list of cache write-back instructions.

17.     (Original) An apparatus in accordance with claim 16, wherein:

said list structure is a full list.

18.     (Original) An apparatus in accordance with claim 16, wherein:

said list structure is a partial list.

19.     (Currently Amended) An apparatus in accordance with claim ~~18~~ 17 , wherein:

said full list comprises one entry per cache line.

20.     (Original) An apparatus in accordance with claim 18, wherein:

said partial list comprises one entry per plurality of cache lines.

21.     (Currently Amended) In a multiprocessor computer system with a plurality of processors and cache memory, an apparatus for cache flushing, comprising:

a list structure for tracking the status of a plurality of cache entries, wherein said

list structure is located outside the cache <u>and wherein said list structure does not contain</u> <u>cache data or addresses</u>;

a processor identification within said list structure for linking each of said plurality of cache entries to one of the plurality of processors;

a query mechanism for checking said list structure for the state of a cache entry identified with a processor;

a cache flush mechanism for flushing a cache entry linked to an identified processor and for modifying said list structure to reflect the flushed status.

22.    (Original)  An apparatus in accordance with claim 21, wherein:

said list structure contains at least one bit for each cache line.

23.    (Original)  An apparatus in accordance with claim 21, wherein:

said list structure contains at least one bit for each of a plurality of cache lines.

24.    (Original)  An apparatus in accordance with claim 21, wherein:

said list structure is located on a die with at least one of the plurality of processors.

25.    (Currently Amended)  A method of flushing a cache, comprising:

creating a table of cache entries separate from the cache <u>and without the cache data</u> <u>or addresses</u>;

tracking modified cache entries in said table; and

generating a write-back command from said table in response to a cache flush

event.

26. (Original) A method in accordance with claim 25, further comprising:

generating an invalidate command in response to a cache flush event.

27. (Original) A method in accordance with claim 25, further comprising:

repeating the procedure for each level of cache.

28. (Original) A method in accordance with claim 25, further comprising:

querying said table in response to a snoop command.

29. (Original) A method in accordance with claim 25, further comprising

writing-back modified cache entries to memory.

30. (Original) A method in accordance with claim 25, further comprising:

writing-back modified cache entries to a high level cache.